

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

FILAMENT ABS GP450

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:filament used in 3D printers.Uses advises against:not determined.

1.3 Details of the supplier of the safety data sheet

Entity responsible:	Spectrum Group Sp. z o.o.
Address:	Parkowa 85, 05-806 Pęcice, Poland
Telephone:	+48 608 109 008

E-mail address for a competent person responsible for sds: biuro@theta-doradztwo.pl

1.4 Emergency telephone number

112

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Product is not classified as hazardous for human life and health and for the environment.

2.2 Label elements

Hazard pictograms and signal words

None.

Names of substances mentioned on label

None.

Hazard statements

None.

Precautionary statements

None.

2.3 Other hazards

Product does not meet criteria for PBT or vPvB in accordance with Annex XIII of REACH Regulation.

Section 3: Composition/information on ingredients

3.1 Substances

Not applicable.

3.2 Mixtures

Product based on acrylonitrile butadiene styrene copolymer with the addition of coloring agents.

CAS Number: 100-41-4	<u>ethylbenzene¹</u>	
EC Number: 202-849-4	Flam. Lig. 2 H225, Asp. Tox. 1 H304, Acute Tox. 4 H332, STOT RE 2 H373	.010/
Index Number: 601-023-00-4		< 0,1 %
Registration Number: —		

¹⁾ Substance with Community workplace exposure limits.

Full text of each relevant H phrase is given in section 16 of SDS.



Section 4: First aid measures

4.1 Description of first aid measures

Skin contact:

Filament: in case of exposure rinse contaminated skin using water with soap.

<u>During printing process</u>: possible thermal burns. Rinse damaged skin with water. Put on sterile dressing. Contact doctor.

Eye contact:

<u>Filament:</u> protect non-irritated eye, remove contact lenses. Rinse contaminated eyes with water for 10-15 minutes. Avoid strong stream of water – risk of damage of the cornea. Contact an ophthalmologist.

<u>During printing process</u>: splashes of liquid filament may cause burns. Put on sterile dressing. Contact an ophthalmologist immediately.

<u>Ingestion</u>: exposure by this route does not typically occur. If swallowed, rinse mouth with water. Do not induce vomiting. Contact a doctor, show container or label.

Inhalation:

Filament: exposure by this route does not occur.

<u>During printing process</u>: remove the victim to fresh air. Keep warm and calm. Consult a doctor, if disturbing symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

There are no significant effects or critical hazards reported under normal conditions of use. Prolonged inhalation of fumes evolved during the printing process may cause headaches, poor concentration, exhaustion.

4.3 Indication of any immediate medical attention and special treatment needed

Physician makes a decision regarding further medical treatment after thoroughly examination of the injured. Symptomatic treatment.

Section 5: Firefighting measures

5.1 Extinguishing media

<u>Suitable extinguishing media</u>: carbon dioxide, extinguishing powder, extinguishing foam, water spray. <u>Unsuitable extinguishing media</u>: water jet – risk of fire propagation.

5.2 Special hazards arising from the substance or mixture

During combustion harmful fumes consisting of carbon oxides and other harmful products of thermal decomposition may be produced. Do not inhale combustion products, it may cause health risk.

5.3 Advice for firefighters

Personal protection typical in case of fire. Do not stay in the fire zone without self-contained breathing apparatus and protective clothing resistant to chemicals. Do not let extinguishing water to reach drainage system, surface water and groundwater. Collect used extinguishing media.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Handle in accordance with good occupational hygiene and safety practices. Ensure that effects of the breakdown are removed only by qualified personnel. Ensure adequate ventilation. Avoid inhalation of fumes evolved during the printing process.

6.2 Environmental precautions

In case of release of large amounts of the product, it is necessary to take appropriate steps to prevent it from spreading into the environment.

6.3 Methods and material for containment and cleaning up

Collect mechanically. Collected material should be reused or treated as a waste.



6.4 Reference to other sections

Appropriate conduct with waste product – section 13.

Section 7: Handling and storage

7.1 Precautions for safe handling

Handle in accordance with good occupational hygiene and safety practices. Use only as intended. In case of rubbing or friction, accumulation of electrostatic charges on the filament surface may occur. Accumulated electric charge can be transferred to the user and may be a source of ignition - use extreme caution when working with flammable materials.

7.2 Conditions for safe storage, including any incompatibilities

Store filament only in a cool, dry place protecting against weather (direct sunlight, frost, precipitation). Protect from sources of fire and naked flames. Do not store with incompatible materials (see subsection 10.5).

7.3 Specific end use(s)

No information about uses other than mentioned in subsection 1.2.

Section 8: Exposure controls/personal protection

8.1 Control parameters

Specification	TWA 8 hour	STEL 15 min
ethylbenzene [CAS 100-41-4]	442 mg/m ³	884 mg/m ³

The table above shows the maximum workplace concentration values on the Community level.

Legal basis: Commission Directive 2006/15/EC, 2000/39/EC, 2009/161/EC, 2017/164/EU, 2019/1831/EU

Please check any national occupational exposure limit values in your country.

Recommended control procedures

Procedures concerning the control over the dangerous components concentrations in the air and control over the air quality in the workplace – if they are available and justified for the position – in accordance with the European Standards, with the conditions within the exposure place and a proper test methodology adapted to the working conditions.

8.2 Exposure controls

Observe good occupational hygiene and safety practices. Do not eat, drink or smoke when using the product. Wash hands thoroughly before breaks and after work.

Hand and body protection

Wear protective gloves and protective clothing if a risk assessment indicates this is necessary.

Eye protection: use tightly fitting protective glasses or face protection if risk assessment indicates that it is necessary.

<u>Respiratory protection</u>: under normal conditions of use is not required. In emergency situation, when exposed to high concentrations of fumes evolved in printing process appropriate respiratory protective equipment should be worn.

Applied personal protective equipment must comply with the requirements of the Regulation 2016/425/EU. The employer is obliged to provide protective equipment relevant to performed activities and in accordance with all quality requirements, including its maintenance and cleaning.

Environmental exposure controls

Avoid release of large amounts of the product to groundwater, drainage system or soil.



Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties physical state/appearance: solid/filament colour: according to assortment odour: characteristic odour threshold: not applicable not applicable pH: melting point/freezing point: 95-105 °C not determined initial boiling point and boiling range: flash point: not determined, product is not flammable evaporation rate: not applicable flammability (solid, gas): not flammable upper/lower flammability or explosive limits: not determined vapour pressure: not applicable vapour density: not applicable density: not determined solubility(ies): not determined partition coefficient: n-octanol/water: not determined auto-ignition temperature: not determined decomposition temperature: > 300 °C explosive properties: not determined oxidising properties: not determined viscosity: not applicable 9.2 **Other information** bulk density: 500-700 g/l

Section 10: Stability and reactivity

10.1 Reactivity

Product is resistant to chemicals. See also subsections 10.3-10.5.

10.2 Chemical stability

The product is stable under normal conditions of handling and storage.

10.3 Possibility of hazardous reactions

Possible exothermic reactions.

10.4 Conditions to avoid

Protect from direct sunlight, sources of fire and heat, excpet from processes connected directly with using of the product.

10.5 Incompatible materials

Strong oxidizers, strong basics.

10.6 Hazardous decomposition products

Carbon oxides, nitrogen oxides.

Section 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.



Skin corrosion/irritation Based on available data, the classification criteria are not met. Serious eye damage/irritation Based on available data, the classification criteria are not met. Respiratory or skin sensitization Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard

Based on available data, the classification criteria are not met.

Section 12: Ecological information

12.1 Toxicity

Product is not classified as hazardous for the environment.

12.2 Persistence and degradability Product is not easily biodegradable.
12.3 Bioaccumulative potential

No bioaccumulative potential.

12.4 Mobility in soil

Product is not mobile in soil.

12.5 Results of PBT and vPvB assessment

Product does not contain ingredients, which meet criteria for PBT or vPvB in accordance with Annex XIII of REACH Regulation.

12.6 Other adverse effects

Product is not classified as hazardous to the ozone layer.

Section 13: Disposal considerations

13.1 Waste treatment methods

Waste material should be stored in designated place for recycling or utilization. Waste product should be recovered or disposed of in authorized incineration plants or waste facility in accordance with local regulations. Recommended waste code: 07 02 13.

Legal basis: Directive 2008/98/EC as amended, 94/62/EC as amended.

Section 14: Transport information

14.1 UN Number

Not applicable. Product is not classified as dangerous during transportation.



14.2 UN proper shipping name

Not applicable.

14.3 Transport hazard class(es)

Not applicable.

14.4 Packing group

Not applicable.

- **14.5 Environmental hazards** Not applicable.
- 14.6 Special precautions for user

Not applicable.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC as amended.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 as amended.

Commission Regulation (EU) No 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste and repealing certain Directives as amended.

European Parliament and Council Directive 94/62/EC of 20 December 1994 on packaging and packaging waste as amended.

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Commission Directive 2006/15/EC of 7 February 2006 establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC.

Commission Directive 2009/161/EU of 17 December 2009 establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC.

Commission Directive 2017/164/EU of 31 January 2017 establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU.

Regulation (EU) No 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC.

Commission Directive 2019/1831/EU of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC.

15.2 Chemical safety assessment

It is not necessary to carry out a chemical safety assessment for the mixture.

Section 16: Other information

Full text of indicated H phrases mentioned in section 3

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H332 Harmful if inhaled.
- H373 May cause damage to organs through prolonged or repeated exposure.



Abbreviations and acronyms

PBT	Persistent, Bioaccumulative and Toxic substance
vPvB	very Persistent, very Bioaccumulative substance
Acute Tox. 4	Acute toxicity category 4
Asp. Tox. 1	Aspiration hazard category 1
Flam. Liq. 2	Flammable liquid category 2
STOT RE 2	Specific target organ toxicity — repeated exposure category 2

<u>Trainings</u>

Before commencing working with the product, the user should learn the Health & Safety regulations, regarding handling chemicals, and in particular, undergo a proper workplace training.

Key literature references and data sources

This sheet was prepared on the basis of on manufacturer's data, literature data, online databases, our knowledge and experience, taking into account the current legislation.

Additional information

Date of issue:	07.08.2020
Version:	1.0/EN
Safety Data Sheet made by:	"THETA" Technical Consulting

The information above is based on a current available data concerning the product, but also on the experience and knowledge in this field of the producer. They are neither a quality description of the product nor a guarantee of particular features. They are to be treated as aid to safety in transport, storage and usage of the product. That does not free the user from the responsibility of improper usage of the information above and also of improper compliance with the law norms in the field.